



中鋼馬來西亞有限公司

CSC STEEL SDN. BHD. (228899-P)

180, Kawasan Industri Ayer Keroh, Ayer Keroh, 75450 Melaka, Malaysia.

Tel : (06) 2310169 (Hunting) Fax : (06) 2315806, 2310167

SAFETY DATA SHEET

1. Chemical Product And Company Identification

Product Name	: Cold Rolled Steel – Medium and High Carbon
CAS No	: Mixture
Manufacturer	: CSC Steel Sdn. Bhd.
Address	: 180, Kawasan Industri Ayer Keroh, Ayer Keroh , 75450, Melaka , Malaysia.
Revision Date	: 31-July-2024
Emergency contact	: 06-2310169

2. Hazards Identification

Hazard symbol: None

Acute Effect:

- Swallowed: Not expected to be swallowed in the form supplied.
- Eye: Excessive exposure to high concentrations of dust may cause irritation to the eyes. Particles of iron or iron compounds, which become embedded in the eyes, may cause rust stains unless removed fairly promptly.
- Skin: Skin contact with dusts may cause irritation or sensitization. Prolonged contact with oil residue may cause skin irritation, dermatitis or allergic reactions in sensitized individuals. Safety precautions (e.g. wear hand gloves) shall be taken to protect against sharp edges.
- Inhaled: Not expected to be inhaled in the form supplied. Welding or cutting operations may generate iron oxide fume.
- Chronic effects: No reports of effects from prolonged or repeated exposure to the product as supplied. Prolonged contact with the surface oil used for corrosion protection may irritate the skin in sensitive individuals.

3. Composition / Information on Ingredients

This SDS covers the series of products consisting of the following components, the concentrations for ingredients are expressed as % by weight.

Base steel	%	CAS No.
Iron	Balance	7439-89-6
Carbon	1.00 Max.	7440-44-0
Manganese	0.90 Max.	7439-96-5
Phosphorus	0.030 Max.	7723-14-0
Sulfur	0.035 Max.	7704-34-9
Silicon	0.35 Max.	7440-21-3

The surface of this product may have low levels of either one of the following chemicals present resulting from the use of various types of anti-corrosion treatments.

Surface Treatment	Proportion	CAS No.
Rust Preventive Oil RP93	<2000 mg/M ²	Mixture



中錫馬來西亞有限公司

CSC STEEL SDN. BHD. (228899-P)

180, Kawasan Industri Ayer Keroh, Ayer Keroh, 75450 Melaka, Malaysia.

Tel : (06) 2310169 (Hunting) Fax : (06) 2315806, 2310167

4. First Aid Measures

- Swallowed: It is unlikely this product can be swallowed in the form of supplied.
- Eye: Flush with large amounts of clean water to remove particles. Seek medical attention if irritation persists.
- Skin: Remove contaminated clothing. Wash affected areas with soap or mild detergent and water. If thermal burn has occurred, flush area with cold water and seek medical attention. If mechanical abrasion occurred, seek medical attention. If the skin is cut during handling, seek medical treatment.
- Inhaled: It is unlikely the product can be inhaled in the supplied form. For over-exposure to airborne fumes, remove exposed person to fresh air. If breathing is difficult or has stopped, administer artificial respiration or oxygen is indicated. Seek medical attention promptly

5. Fire Fighting Measures

Not flammable in its solid state.

6. Accidental Release Measures

Not applicable to steel in its solid state.

7. Handling and Storage

- Normal handling: Wear Personal Protective Equipment at all time to handle this sharp edge of thin sheets or coils. All employees should be trained to handle this product safely.
- Storage Recommendations: Store in a facility will prevent products from physical damage, moisture, and direct sunlight.

8. Exposure control/Personal Protection

Hand protection: Protective gloves shall be worn in material handling, welding and burning process.

9. Physical and Chemical Properties

Appearance : Matte or Bright finish, becomes reddish brown with oxidation

Physical state: Solid

Odor : Odorless

pH : N/A

Viscosity : N/A

Water solubility : Insoluble

Other solubility: N/A.

Boiling point/ range: @1atm Approx.3000°C

Evaporation rate: N/A.

Flammable limit: N/A.

Explosion limit : N/A.

10. Stability and reactivity

Stability	Stable under normal temperatures and pressure.
Reactivity	Stable under normal condition.
Incompatibilities	Product can be attack by moisture and corrosive materials.
Hazardous decomposition product	Toxic vapors and metallic fumes may be release if ignited or melted in a fire



中鋼馬來西亞有限公司

CSC STEEL SDN. BHD. (228899-P)

180, Kawasan Industri Ayer Keroh, Ayer Keroh, 75450 Melaka, Malaysia.

Tel : (06) 2310169 (Hunting) Fax : (06) 2315806, 2310167

11. Toxicological information

No relevant toxicological data found at time of research.

12. Ecological information

No ecological concern identified.

13. Disposal Consideration

Steel scraps shall be recycled whenever possible.

14. Transport Information

No special transportation classifications.

15. Regulatory Information

Disposed of in accordance with local, state, federal regulations.

16. Other Information

This information is the best of our current knowledge and to describe our product in term of health and safety and environmental requirement. As the conditions of handling, use, and disposal of this product are beyond manufacturer control, the recommendation or suggestion are made without guaranteed.